



UNISTEP POLISH

Unistep Polish is a modern maintenance product for lacquered wood floor surfaces. Polish can also be used on laminate, vinyl, PVC or linoleum. It dissolves itself with each new application and does not build up layers. Polish contains lacquer particles and it prevents the floor from visual signs of aging and wear. Maintenance with Polish is recommended after every 5th cleaning.

DIRECTIONS FOR USE

Recommended working temperature is between 13°C (55°F) and 25°C (77°F). Clean with Unistep Cleaner. The floor must be free from contamination and dust. Any residual polish or grease must be carefully removed with Unistep Remover and a sanding screen grit 120.

Floors which previously have been treated with polish or wax have to be deep cleaned before using Polish. Pour Unistep Polish directly onto the floor from the can. Do not dilute Polish. Disperse Polish with a clean, damp mop or lint-free cloth. Let it dry for about 1 hour.

After that the floor is ready to use. If streaks appear it is likely that the floor has been treated with polish or wax. In that case it has to be deep cleaned with suitable polish/ wax remover.

FREQUENCY OF USE

To maintain the look and the protective properties of the lacquer, we recommend an application of Unistep Polish after every fifth clean with Unistep Cleaner.

TECHNICAL DATA

VOC: 0 g /l (EU limit value for this product (cat. A/i): 140 g/l (2010) 2004/42/CE)

Content: Copolymer-Acrylate; Ammoniac solution.

Solid content: 4%

pH: 8,5

Coverage: 60 m²/l

Recommended Use: For maintenance and cleaning of different floor types.

Odour: Very light, non-offending

Drying time: Approx. 1 hour.

Safety/Toxicity: Non-hazardous / Not classified

Packaging: 1 litre plastic cans

Storage and transport: Best before 12 months at 5°C to 25°C in unopened package. Protect from frost.

Shelf life: See expiration date on canister.

Chemical Resistance: Resistant to grease, water and ordinary household cleaners and detergents.

Cleaning of tools: Clean tools with water, before the refresher has dried.

Disposal: Dispose it in accordance to local regulations.

Maintenance: Dry cleaning is recommended on all oiled surfaces. If necessary clean with Unistep Cleaner. Do not leave water on the floor. If the floor is heavily worn, maintain with Unistep Care Oil.

There are no express or implied warranties, including warranties of merchantability and/or fitness for a particular purpose. Buyers' remedies are limited to replacement or refund of the purchase price. Manufacturer assumes no liability for injuries, incidental or consequential damages. User shall determine suitability of product for intended use. The information and recommendations in this data sheet are guidelines for application and are not to be construed as a guarantee. In all cases it is the responsibility of the user to determine if the product is suitable for the purpose, and complete a successful application. Unistep can only guarantee the delivered product. If the user is in doubt we would recommend a preliminary onsite test. Please ensure you have read and understood all information on the labels and in the safety data sheets before using this product. This data sheet replaces all previous versions.

